



- 1 — 4
- 2 — 3
- 3 — +
- 4 — Middle
- 6 — 2
- 7 — GND — 1 — 1
- 8 — 2
- 9 — 1
- 10 — 2
- 11 — -
- 12 — Tip
- 14 — 3
- 15 — 3

NOTE: All relevant materials are complied with RoHS directive.

8	XLR Female 3Pin Assembly Type plug , Nickel Plated front body	2	Analogue input.
7	DC3.5 Stereo Socket with assembly hood black	1	Headphone.
6	DC5.5*2.5 Jack with assembly hood black	1	DC Power In.
5	UL2464 22AWG 2C Cable (Red+Black)	1	
4	Metal hood with long thumb screw and locked by two sets of screw	2	
3	USB A Male Solder Type	1	
2	UL2725 28Awg 1P+24Awg 2C+AEB OD4.5 Black		
1	DB15 MALE GOLD FLASH ON CONTACTS	1	
No.	DESCRIPTION	Q'TY	Supplier

APPROVED		DK-Technologies A/S, Marielundvej 37D, DK-2730 Herlev, Denmark.	Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm	
CHECKED				
DRAWING				
DATE	13/Dec/13			
ITEM NO.		DK T7 Breakout cable.	UNIT:mm	